

NB4 LED SERIES PORTABLE HANDLAMPS 240VAC



- Robust maintenance free construction
- Highly efficient replaceable T8 LED tube
- Integrated endcap On/Off switch with LED power on indicator light
- Thermoplastic anti-roll finned end caps
- Advanced polycarbonate UV stabilised outer case with internal prisms and opal diffuser
- Oil, petrol and corrosion resistant
- Red colour coded endcap and cable to reflect the voltage (240VAC)
- Removeable hanging hooks
- Heavy duty PVC sheathed 6.0m lead with 2-Pin plug
- Operating temperature range -20°C to +40°C
- Impact resistant rating IK07
- Environmental protection IP65

CERTIFICATION	IP RATING	CABLE			
SAA	IP65	6m with 2-Pin Plug			
IK RATING	BOX CTN QTY	01			
IK07		1 1			

DIMENSIONS (mm)						
880mm						
1505mm						

Part No.	Voltage	Power (W)	Current (A)	ССТ	Ra	Lumens	Lifetime hrs	Weight (kg)	Length (L x Dia)mm
VERNB418240VLED	90 - 265VAC	10W	0.36	5000K	80	1060	50,000	1.2	880 x ø86
VERNB436240VLED	90 - 265VAC	20W	0.42	5000K	80	1924	50,000	1.7	1505 x ø86





