

**NEW****TRADE\$AVE**

# 150 & 200W LED Highbays

**IPART  
VEU  
APPROVED****Features**

- Aluminium housing powder coated black
- Tempered glass lens
- Low profile design
- Surge protected 4kV Line-Line
- High efficiency SMD chip 150Lm/w
- Operating Temp: -30°C to +50°C
- 1.5m flex & plug 3 pin
- IP65 rated IK08
- Multi-wattage 100/120/150/200W (available on 200W model only)
- Plug-and-play microwave and Lux sensor with remote control option
  - 12m mounting height @ 1-8m diameter detection range
  - Lux level adjustment
  - Sensitivity adjustment
  - Time on/off adjustment up to 30min
  - Light harvesting



TSANT-5-4T



TSRC-100

CERTIFICATION	IP RATING	DALI DIMMABLE
PROTECTION	BOX   CTN QTY	
	<b>1   2</b>	

DIMENSIONS (mm)	
TSHB150W	TSHB200W

Part No.	Voltage AC	Watt	PF	CCT	Ra	Lumens	Beam Angle	Lifetime hrs	Fitting Colour	Dimensions (H x D)mm
TSHB150W	200-240V	150W	0.9	5000K	80	22,500	120°	50,000	Black	167 x 298
TSHB200W	200-240V	100-200W	0.9	5000K	80	15K, 18K, 22.5K, 30K	120°	50,000	Black	166 x 364

Part No.	Description
TSHB150W	LED 150W Highbay DALI Dimmable 5000K
TSHB200W	LED 200W Highbay DALI Dimmable 5000K Multi Wattage 100-120-150-200W
TSANT-5-4T	Microwave/Lux Sensor Plug & Play to suit TSHB200W & TSHB150W Highbays
TSRC-100	Remote Control for the TSANT-5-4T Microwave/Lux Sensor
TSBC-H28-02A	Adjustable Wall/Ceiling Bracket to suit TSHB200W & TSHB150W Highbays

**1300 555 586**  
**repelec.com.au**

**rep ELEC**  
**TRADE SOLUTIONS**

**@RepelecAU**