

EMERGENCY & EXIT LIGHTS

LED Recessed Emergency Downlight



Features

- VO flame retardant ABS
- Non-maintained
- Energy efficient LED, low 0.5W standby power consumption
- Superior light output, D80 spacing classification to cover most applications
- Tamper resistant, no dome required
- Lithium Ion battery 3.2V, 1500mAh
- 3 hour emergency battery run-time
- Self testing
- Operating temp: -0°C to +40°C
- Plug & play connections for ease of installation
- Complies with AS/NZ2293
- IP20 rated

Part# TSSD1

LED Surface Mount Emergency Downlight



Features

- VO flame retardant ABS
- Non-maintained
- Energy efficient LED, low 0.5W standby power consumption
- Superior light output, D40 spacing classification to cover most applications
- Tamper resistant, no dome required
- Lithium Ion battery 3.2V, 3200mAh
- 3 hour emergency battery run-time
- Self testing
- Large terminal block & cable entry
- Operating temp: -0°C to +40°C
- Complies with AS/NZ2293
- IP20 rated

Part# TSSD1SM

Universal Surface Mount Exit Light



Features

- Polycarbonate body and diffuser
- Wall and ceiling mount
- Energy efficient LED, low 3W standby power consumption
- Superior light output, 24m viewing distance
- Lithium Ion battery 3.2V, 1500mAh
- 3hrs emergency battery run-time
- Self testing
- Large terminal block and cable entry
- Operating temp: -0°C to +40°C
- IP20 rated
- Complies with AS/NZ2293

Includes the following decals

- Standard running man
- Running man with left arrow
- Running man with right arrow

Part# TSESC

Surface Mount Blade Exit Light



Features

- Polycarbonate body and diffuser
- Wall and ceiling mount
- Energy efficient LED, low 3W standby power consumption
- Superior light output 24m viewing distance
- Lithium Ion battery 3.2V, 1500mAh
- 3hrs emergency battery run-time
- Self testing
- Large terminal block and cable entry
- Operating temp: -0°C to +40°C
- IP20 rated
- Complies with AS/NZ2293

Includes the following decals

- Standard running man
- Running man with left arrow
- Running man with right arrow

Part# TSEBW

Recessed Blade Exit Light



Features

- Polycarbonate body and diffuser
- Ceiling mount
- Energy efficient LED, low 3W standby power consumption
- Superior light output 24m viewing distance
- Lithium Ion battery 3.2V, 1500mAh
- 3hrs emergency battery run-time
- Self testing
- Large terminal block and cable entry
- Operating temp: -0°C to +40°C
- IP20 rated
- Complies with AS/NZ2293

Includes the following decals

- Standard running man
- Running man with left arrow
- Running man with right arrow

Part# TSEBR

Surface Mount Exit Light - Jumbo



Features

- Polycarbonate body and diffuser
- Wall and ceiling mount
- Energy efficient LED, low 3W standby power
- Superior light output 40m viewing distance
- Lithium Ion battery 3.2V, 3200mAh
- 3 hours emergency battery run-time
- Self testing
- Large terminal block and cable entry
- Operating temp: -0°C to +40°C
- IP20 rated
- Complies with AS/NZ2293

Includes the following decals

- Running man with left arrow 2 pieces
- Running man with right arrow 2 pieces
- Running man face left 2 pieces
- Running man face right 2 pieces

Part# TSJST40

Purchase from your Electrical Wholesaler